

OMEXCO
Fine Belgian Wallcoverings




HIGH PERFORMANCE
ESSENCE




NB: The portrayed colours may differ from reality.

References HPE4 - SILK
Composition: textured wallpaper
Weight: $\pm 270 \text{ g/m}^2$ ($\pm 7.96 \text{ oz/sq yd}$)
Custom colouring: 300 m / 330 yds min.
The wallcovering can be installed vertically or horizontally



Width of the wallcovering.



Pattern repeat is 0 cm (0") and the design does not need to be matched.



Fire resistant:
EU: B, s1-d0
US: class A




This design requires reverse hanging.



Scrubbable.



Light resistant:
Xeno test 7.




Breathable.



Apply a ready mixed PVA or EVA clear adhesive directly to the wall, no need to humidify the back of the wallcovering.



Ecological.



Totally or virtually seamless.



Sold by the metre/yard. No minimum.



100% Recycled PET fibres.



Printed with solar energy.



ISO 105-E03:2010
Cleanable with chlorinated products.



Product complying with the council directive 2014/90/EU on marine equipment.



Product in compliance with the fire protection requirements of the Merchant Shipping (Marine Equipment) Regulations 2016 (MSMER).



Printed with water soluble inks and without heavy metals.



Strong and resistant.



Antibacterial finish.

More information and samples are available on request.

Omexco n.v. - Ambachtenlaan 12 - 3001 Heverlee - Belgium
t. +32 16 40 18 80 - info@omexco.com - www.omexco.com